



SKORPION Trapped Key Interlocking - ISOLATION

ISOLATION SWITCH WITH SOLENOID CONTROL (PANEL MOUNT) IP65 RATED - ISP-SKR-WR:

ISP-SKR-WR



Fitted with RED/GREEN status lamps.

All isolation available with Stainless Steel 316 or Mirror Polished Die Cast Metal Barrel

In addition to the 4 pole main isolator contacts, all models of the isolation switch ISP-SKR-WR are supplied with:

RED lamp wired to indicate solenoid energized.

GREEN lamp for end user designation.

2NC 1NO monitoring contact block.

Solenoid energised to release key.

Ingress Protection: IP65.

Power "ON" = Key TRAPPED. Power "OFF" = Key can be RELEASED

ISP-SKR-WR STAINLESS STEEL 316

Sales Number	WATER RESISTANT ISOLATION SWITCH PANEL MOUNT SOLENOID KEY RELEASE			
	RATING			SOLENOID VOLTAGE
SS-ISP-SKR-WR-25	25A	690V	4 pole	24V ac/dc
SS-ISP-SKR-WR-40	40A	690V	4 pole	24V ac/dc
SS-ISP-SKR-WR-63	63A	690V	4 pole	24V ac/dc

(ISP-SKR-WR DIE CAST METAL (Mirror Finish

Sales Number	WATER RESISTANT ISOLATION SWITCH PANEL MOUNT SOLENOID KEY RELEASE			
	RATING			SOLENOID VOLTAGE
M-ISP-SKR-WR-25	25A	690V	4 pole	24V ac/dc
M-ISP-SKR-WR-40	40A	690V	4 pole	24V ac/dc
M-ISP-SKR-WR-63	63A	690V	4 pole	24V ac/dc